Stratus[™] Horizontal Wrapper Economic Pillow-Pack Packaging of Food and Non-Food Products

Doboy Inc.





Protective, Appealing and Economical Packaging

Easy Operation

This low-cost electronic horizontal wrapping machine comes with electronic controls that offer fast and precise product changeover capabilities equivalent to machines three to four times the price. Installation and start-up of the Stratus takes just two hours! And its compact design offers production layout flexibility.

The Stratus is perfect for a wide variety of products from hardware, bakery, candy, housewares and many other industries.

Package Quality

Quality package seals, tightness and appearance are easily achieved with two sets of finwheels in conjunction with the inclination roller. A "no-tool-required" handwheel for centering the end seal adds the final touch. Three independent servo motors for driving the infeed chain, film feed and end seal crimpers assure consistent control of product, package material and sealing. Also, the Stratus design eliminates drive chains, belts and variators. The result is less maintenance, less wear and greater consistency in machine operation and package quality.



Features

- Twenty pre-programmable product setups.
- Film jog aids in making film changeovers.
- Infeed conveyor with stainless steel product guides provides ample room for hand feeding and meets FDA sanitation requirements.
- Compact design for easy maneuvering into smaller production areas.
- Torque sensitive servo motors stop the machine if jams occur in the infeed or end crimpers.
- Precise heat controls with digital setpoints and out-ofrange alarms assure consistent seal quality.
- Optional Electronic Two-way Eye Correction precisely positions printed film on the package and minimizes film waste created during setup.
- Two sets of finwheels.
- Full range of adjustable formers.

Easy to understand control panel improves operation efficiency with features such as on-the-fly product centering and optional printed film positioning.





Package Specifications

	Length	Width	Max. Height
Single Crimp 120mm diameter (standard)	4" - 14 3/4" (100 mm - 370mm)	1/2" - 8 1/4" (13 mm - 209mm)	2 1/2" (63mm)
Single crimper	4" - 18"	1/2" - 8 1/4"	3 3/4" (95mm)
150mm diameter	(100mm - 460mm)	(13 mm - 209mm)	
Two-up crimper	3" - 7 1/4"	1/2" - 8 1/4"	2 1/4" (57mm)
120mm diameter	(75mm - 185mm)	(13 mm - 209mm)	
Two-up crimper	3" - 9"	1/2" - 8 1/4"	3 1/2" (85mm)
150mm diameter	(75mm - 230mm)	(13mm - 209mm)	


NOTE: Optional Wide sealing jaws available - 9" (230mm) wide crimper

Technical Data

Machine Weight	900 lbs. (410kg)
Power	220VAC, 50/60Hz, 1 phase NEMA 1
Web Specifications	Max. Width 18 1/2" (470mm)
	Max. Diameter 16" (400mm)
Core Diameter	3" (75mm)
Production speed	20 to 150 packages per minute
	(with a two-up crimper arrangement)

Specifications subject to change without notice.

Detailed View




Available Options

- Configuration for larger products
- Date/product identification coder
- ▶ Hole punch crimpers
- Zig-zag knife

Two-up crimpers < existence</p>

- No product no paper
- Stainless steel construction

Stratus Mechanical Dimensions



Doboy Inc. A Bosch Packaging Technology Company

869 South Knowles Avenue New Richmond, WI 54017 USA Phone (715) 246-6511 Fax (715) 246-6539 sales@doboy.com www.doboy.com

Printed in U.S.A.



