

# FETTE

## Electrical rating card

WILHELM FETTE GMBH PRÄZISIONSWERKZEUG- UND MASCHINENFABRIK

Type of current	3ph
Frequency	60Hz
Operating voltage	460V
Control voltage 1	24V-
Control voltage 2	220V
Valve voltage	24V-
Magnet voltage	24V-
Lighting voltage	220V
Pilot lamp voltage	24V-
Current rating	20A-

Ratings for  
3-ph. 380V 50Hz operation

M20; Main drive  
4,00kW; 8,8A; 1500 min<sup>-1</sup>

M30; Hydraulic pump  
0,75kW; 2,2A; 1500 min<sup>-1</sup>

M31; Lubricating pump  
0,12kW; 0,5A; 1500 min<sup>-1</sup>

M32; Dust extractor  
1,10kW; 3,7A; 3000 min<sup>-1</sup>

M50; Fill-o-matic  
0,34kW; 1,5A; 0-4000 min<sup>-1</sup>

Maschinentyp, Maschinenummer; Fremdsprache

P 1000 Nr.298

Kunde, Kommissionsnummer

Abbot, USA  
04/35 487 M

Sonder- und Zusatzausrüstung

- = Datacontrol system  
in accordance with 2138800
- + Basic package 2138801
- + Initial compression  
package 2138802
- + Filling dept regulation  
package 2138803
- = Switch cabinet on rollers
- = Switch cabinet and base in V2A  
+ 2134202 +2134204 :2136407  
-2134201 -2134203
- = Voltage stabilizer, 60Hz type  
+ 2130401 :2136407 -2130400

Identity number 2136400

Parts list

Equipment layout 623-93-06-01-065

Functional diagram 623-81-00-01-009

Wiring diagram 623-91-06-02-027

Electr. layout diagram 623-93-06-01-063

Plug connection 623-93-06-01-064

Control panel 622-93-61-15-041

Switchboard 623-93-60-18-111

Switch cabinet 623-12-01-18-051

Montage

Schaltschrank